

CT-DP1220

DOUBLE SIDE SELF-ADHESIVE TAPE

FEATURES:

- ◆ Aggressive synthetic rubber adhesive
- ◆ High peel adhesion
- ◆ Strong initial tack
- ◆ Temperature and aging resistance

TYPICAL APPLICATION:

- ◆ Aggressive adhesive designed to seal foam, felt, paper based and plastic film surfaces



CT-DP1220			TEST METHOD
Construction	Paper Tissue Carrier // Synthetic rubber adhesive// Double side silicone paper liner		
PROPERTIES	Metric	English	
Total Thickness	120 Micron	4.7 mil	PSTS-33 / ASTM D 3652
Peel Adhesion	20 N/25mm	72 Oz/inch	PSTC-1 / ASTM D 3330
Rolling Tack (11 mm ball)	20 cm	8 inch	PSTC-6 / ASTM D 3121
Tensile strength	50 N/25 mm	11.2 Lb/inch	PSTC-31 / ASTM D 3759
Elongation	4%	4%	PSTC-31 / ASTM D 3759
Service Temperature	-10 ~ +60 °C	14 ~ + 140 °F	-----
Core I.D.	76mm	3"	
Roll width	50mm (2"), 60mm, 75mm (3")		
Roll length	30m (100'), 45m (50 yards), 50m, 100m		

1. The data above are typical results from tests conducted on samples taken from production runs and may be updated without notice. Typical values are not intended to be used for specification development.
2. The product should be stored in the original packaging material at 20 +/- 5°C and 40-60% relative humidity and protected from direct sunlight, heat and moisture. Shelf life: One year when stored at the conditions described above.
3. The surface to which the tape is applied must be clean, dry, free of grease and oil and other contaminants and deposits. Recommended temperature of application: 50 – 105 °F (10 – 40 °C).
4. The user is responsible for determining whether the product is fit for a particular surface and suitable for user's application. The user should make necessary tests and trial-application of the tape to confirm suitability for user's special purpose and method of application.
5. Self adhesive tapes are designed for sealing applications only. In the instance when the sides of the joint are subject to mechanical stress, both sides should be securely positioned using appropriate fasteners or hangers prior to the self adhesive tapes application.
6. Calem Technology warranty that the product is free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment, Calem Technology shall, upon notification thereof and substantiation that the product have been stored and applied in accordance with the above requirements, at Calem Technology discretion, replace or credit the product's purchasing price equivalent.
7. Limitation of liability. Calem Technology Inc. and seller of CT Tape products will not be liable for any loss or damage arising from the CT Tape product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



CT TAPE

1-604-277-6643
186 - 8120 No.2 Road.
Richmond, BC
V7C 5J8, Canada